

IMPORTANT: Due to constant improvements in vehicle design and quality, changes to a vehicle configuration may occur or an error exists which affects the Owner's Manual after the supply for production has already been printed.

The transmission oil imperial capacity is incorrect. However, the metric capacity (0.6 L) is correct:

- **2024 CFORCE 800-1000 (G3) Owner's Manual – Page 11.**

INTRODUCTION		
Items	CFORCE 800/850 TOURING	CFORCE 1000 TOURING / OVERLAND
Bore x Stroke	91mm x 61.5mm	91mm x 74mm
Displacement	800cc	962.6cc
Compression Ratio	10.8:1	
Starting System	Electric Starter	
Lubricating System	Pressure / Splash Lubrication	
Engine Coolant:	CFMOTO uses Organic Acid Technology (OAT) coolant in all liquid-cooled engines. Do not mix with inorganic (IAT) coolant.	
Type		
Volume		
Mixed Ratio:	50% coolant / 50% distilled water	
Engine oil:	SAE 10W-40 SAE 5W-40 / SAE 15W-40 (cold weather) (hot weather)	
Type		
Alternative Viscosity		
Oil Change with Filter	2.32 qt. (2.4 L)	
Transmission oil:	75W-90 GL-5 20 oz. 1.5 qt. (0.6 L)	
Type		
Oil Change		

11

An updated version of this Owner's Manual can be found on the CFMOTO Dealer Portal or the consumer website at www.cfmotousa.com.

CFMOTO regrets the error, and assures consumers of our 100% commitment to the production of high-quality vehicles for powersports enthusiasts to enjoy.